

SPECIFICATIONS

Product Line	Foundations GlueDown
Product Type	Luxury Vinyl Plank (LVP)
Core Material	1.6mm Virgin Vinyl
Fiberglass Reinforced	FiberBlend
Wear Layer	6mil ScratchGuard
Overall Thickness	1.6mm (0.063")
Nominal Plank Size	7" x 48"
Actual Plank Size	177.8mm x 1219.2mm
Edge Profile	Square Edge
Embossing	Natural Wood Texture
Finish	Enhanced Polyurethane System
Installation Type	GlueDown
Bacteria Resistance	Standard



PALLET	
Cartons	55
Square Feet	3597 sqft
Weight (lbs)	2293.25 lbs
Square Meters	333.85 m2
Weight (kg)	1040.2 kg

CARTON	
Planks	28
Square Feet	65.40 sqft
Weight (lbs)	41.09 lbs
Square Meters	6.07 m2
Weight (kg)	18.64 kg

CONTAINER	
Cartons	1,100
Square Feet	71940 sqft
Weight (lbs)	45864.91 lbs
Square Meters	6677 m2
Weight (kg)	20804 kg

PERFORMANCE TESTING

Slip Resistance	ASTM D2047	>0.66 (Dry)
Radiant Flux	ASTM E648	Class 1
Static Load	ASTM F970	2,000 PSI .005 Inch
Smoke Density	ASTM E662	Passes
Light Resistance	ASTM F1515	Passes
Heat Resistance	ASTM F1514	Passes
Chemical Resistance	ASTM F925	Passes
Phthalates	ASTM F3414 - 20 (CPSC)	Passes
Heavy Metals	ASTM F963	Passes
Formaldehyde	ASTM D6007	Passes
FloorScore Certified	California 01350	Passes
Leed Scorecard	EQ 4.3 Low-Emitting Materials	1 Point

WARRANTY

10 TEN YEARS RESIDENTIAL	03 THREE YEARS LIGHT COMMERCIAL	00 NONE HEAVY COMMERCIAL
---------------------------------------	--	---------------------------------------



ARCHITECTURAL SPECIFICATION

All floors shown in the finish schedule or listed in the specification shall be Foundations GlueDown Floor Vinyl Flooring provided by Urban Surfaces Inc., in design and color (list color TBD) selected from the range currently available from Urban Surfaces Inc, having a nominal total thickness of (Foundations GlueDown- 1.6mm-0.063") gauge, and size in 7 in. x 48 in. (Studio 12 GlueDown - 177.8 mm x 1219.2 mm). consisting of a (Foundations GlueDown- 12 mil) thick wear layer over a printed film. Flooring meets composition, size, thickness, squareness, flexibility, resistance to chemicals, resistance to heat and resistance to light requirements of ASTM F 1700, "Standard Specification for Solid Vinyl Tile," Class III, Type B - Embossed Surface. For Foundations, shall have a 3-Year Limited Light Commercial warranty against manufacturing defects. For Foundations GlueDown, the approved adhesives are: Prism 3010, Everlast 3020, and Omni 3050 and Underlayment FloorSilencer Pro. For additional installation, maintenance, or technical information, visit our website at www.urbansurfaces.com or contact us at 1-800-492-8722. Please view actual product samples when making a selection as our printed colors may vary from actual product.

INSTALLATION

End Use:

Residential

Suitable Grade Level:

All grades where excessive moisture conditions do not exist

Installation Method:

Glue Down

Installation Sundries As Required:

3010 Prism, 3020 Everlast, 3050 Omni, Infiniti Moisture Barrier

URBAN SURFACES
2380 RAILROAD STREET BUILDING 101 CORONA, CA
(800)492.8722