



For GlueDown Flooring



NOISE MITIGATION

Reduces noise transfer between wood or concrete based floors.



MOISTURE PROTECTION

Dissipates topical moisture from spills and allows subfloor vapor emissions to breathe.



ANTIMICROBIAL DEFENSE

Protection throughout the pad against mold and mildew.



INSTALLATION METHODS

Single Gluedown Installation

1. Roll out underlayment to float over subfloor and butt seams together.
2. Apply quality pressure-sensitive adhesive on top of the underlayment for floor adhesion.
3. Follow flooring manufacturer's installation instructions.

Double Gluedown Installation

1. Roll out underlayment and butt seams together.
2. Adhere to subfloor using flooring manufacturer's recommended pressure sensitive adhesive, trowel, and install method.
3. Roll over underlayment with a 75 or 100 pound roller.
4. Adhere flooring over top using manufacturer's recommended pressure sensitive adhesive and trowel size.

APPROVED SUBSTRATES

- ✓ Dry, Completely Cured Concrete (at least 28 days old)
- ✓ OSB (approved for use over properly prepared OSB)
- ✓ Cement Backer Units (CBU)
- ✓ Interior Plywood

All wood and concrete subfloors must be flat within 1/8" over a 6' span, or 3/16" over a 10' span. All areas must be checked prior to installation. Not a suitable underlayment for ceramic tile, sheet vinyl, carpet, or VCT. Follow the finished floor covering manufacturer's instructions regarding moisture restrictions when installing over a concrete subfloor.

PRODUCT SPECIFICATIONS

100 sqft Rolls | 70 Rolls Per Pallet | 18 Pallets Per Truck | 1,260 Rolls per Truck

Size	3' x 33.33' roll
Coverage	100 sqft per roll
Density	62.4 lbs/ft ³
Moisture Tolerance	3.5 lbs/1000 ft ² /24 hrs
Perm Rating	2.46 Perm
Thickness	1.25 mm
Weight	34 lbs per roll
R-Value	0.543-hr-ft ² -degf/btu (5.75/inch)
Material	High-Density Synthetic Rubber
Compression Resistance at 50%	68.1psi
Shore A Hardness	63

70
HIIC

68
LIIC

67
IIC

23
ΔIIC

27
ΔHIIC

61
STC

All sound testing performed with SoHo Square flooring.

Sound Testing By
Veneklasen Associates



(800) 496-8722
Sales@urbansurfaces.com

Revised May 17, 2024