

URBAN
SURFACES



OMNI

3050 | ADHESIVE & MOISTURE BARRIER



OMNI

3050 | ADHESIVE & MOISTURE BARRIER



Available In: 2 Gallons

NO TESTING, NO FLASH TIME

Get started immediately. Omni™ has zero flash time and lets you skip the RH, pH, and MVER testing to save valuable time on your project.



OMNI™
DETAILS

THE ALL-IN-ONE-STEP ADHESIVE FOR FLOORING

- ✓ Low VOC, Extremely Low Odor
- ✓ No pH Testing Required
- ✓ Plasticizer Migration Resistance
- ✓ Self-Priming
- ✓ No Wait, Zero Flash Time
- ✓ No Moisture Testing Required



100% MOISTURE PROTECTION



INSTALL IMMEDIATELY, NO TESTING REQUIRED



COMMERCIAL-GRADE BOND

Zero
Flash Time

4 hrs
Heavy Traffic

6 hrs
Cure Time

8 hrs
Rolling Loads

REQUIRED TOOLS



U-Notch Trowel
For Porous Substrates
Coverage: ~ 220-260 sqft/gal



75 lb Floor Roller
For Rolling and Cross-Rolling a Complete Installation

ENHANCE ANY SPACE WITH COMFORT AND QUIET

When it comes to adhesive, Omni™ does it all in one step. Take your whole project one step further with our FloorSilencer™ underlayments. These pads and rolls provide multi-level noise reduction, moisture control, thermal insulation, leg-joint comfort, and more.



ADHESIVE WITH 100% MOISTURE PROTECTION IN ONE STEP

MAXIMUM OCCUPANCY, MAXIMUM COMFORT

With low VOC emission and extremely low odor, Omni™ allows occupants to move in quickly. With a quick install timeline, spaces will stay occupied with minimal interruption.

SPECIALLY FORMULATED FOR COMMERCIAL USE

Heavy foot traffic and rolling loads are no match for Urban Surfaces' Omni™ and our durable LVT flooring.



EXPLORE ALL OF THE URBAN ESSENTIALS™

Start to finish, the Urban Essentials™ line contains everything needed for the perfect flooring installation.

(800) 492-8722 | Info@UrbanSurfaces.com | 2380 Railroad Street, Bldg 101, Corona, CA 92878