

URBAN
SURFACES



VANGUARD

3202 | WOOD ADHESIVE & 90% MOISTURE BARRIER



VANGUARD

3202 | WOOD ADHESIVE & 90% MOISTURE BARRIER



Available In: 4 Gallons

FAST-ACTING, RELIABLE, AND ECO-FRIENDLY ADHESION

Vanguard™ is a strong adhesive specifically engineered for Urban Surfaces' wood flooring. Easy to clean, low odor, and isocyanate-free, it features a fast-curing, early-grab formula that minimizes project time and labor.



PARAGON™
DETAILS

POWERFUL PERFORMANCE FOR GLUEDOWN **WOOD FLOORING**

- ✓ Strong Early-Grab Formula
- ✓ Extremely Low Odor and VOCs
- ✓ Contributes to LEED Certification
- ✓ Alkaline Resistant, Elastomeric Bond
- ✓ Solvent and Isocyanate-Free
- ✓ 1 Part Installation, No Stirring/Mixing



**PROTECTS FROM
ALKALI ATTACK**



**90% MOISTURE
RESISTANCE**



**HEAVY-COMMERCIAL
ELASTOMERIC BOND**

0 mins
Open Time

12 hrs
Cure Time

45-60 mins
Working Time

6 hrs
Foot Traffic

REQUIRED TOOLS

 **75-100 lb Floor Roller**
For Rolling and Cross-
Rolling a Complete
Installation

for Bond Only

 **Square-Notch Trowel**
Size: $\frac{1}{8}$ " x $\frac{1}{8}$ " x $\frac{1}{8}$ "
Coverage: ~ 60-70 sqft/gal

 **V-Notch Trowel**
Size: $\frac{3}{16}$ " x $\frac{1}{4}$ " x $\frac{5}{16}$ "
Coverage: Up to 50 sqft/gal

for Moisture Barrier

 **V-Notch Trowel**
Size: $\frac{1}{4}$ " x $\frac{1}{4}$ "
Coverage: ~ 25-30 sqft/gal

 **V-Notch Trowel**
Size: $\frac{1}{2}$ " x $\frac{15}{32}$ "
Coverage: Up to 20 sqft/gal

SKIP THE COSTLY CONSTRUCTION DELAYS AND SAVE BIG

Avoid weeks of potential delays by starting your installations right away. Eliminate the need for bead blasting, skim coating, and 2-part epoxy systems. Take control of your projects and keep your schedule on track every step of the way.



STRENGTH YOU CAN COUNT ON

MAXIMUM OCCUPANCY, MAXIMUM COMFORT

With extremely low VOC emission and odor, Paragon™ allows occupants to move in quickly. With minimal wait time for post-install foot traffic, spaces can stay occupied with very little interruption.

STRONG, BUT FLEXIBLE ELASTOMERIC BOND

Forms a strong yet flexible bond that allows the flooring to expand, contract, and move with seasonal changes in temperature and humidity without losing adhesion or causing damage.

INSTALL QUICKER! NO PRIMER NEEDED.

Because this product is designed for porous subfloors, the use of any primer would inhibit the performance of the wood adhesive.



EXPLORE ALL OF THE URBAN ESSENTIALS™

Start to finish, the Urban Essentials™ line contains everything needed for the perfect flooring installation.

(800) 492-8722 | Info@UrbanSurfaces.com | 2380 Railroad Street, Bldg 101, Corona, CA 92878